

Balsawood Bridge Competition 2024

Contact: Jamie Francisco at jfrancisco@silvercreekschools.org

Goal: Engineer and construct the strongest, yet most efficient bridge for a 16" or 18" span, using 1/8" x 1/8" balsa or basswood wood members and glue.

Middle School: 16" free span between testing blocks.

High School: 18" free span between testing blocks.



Efficiency will be measured by comparing the measured lbs. of weight *held* divided by the weight of the actual bridge in grams.

$$\frac{\text{Weight held (lbs.)}}{\text{Weight of Bridge}} = E_{Br} \text{ lbs./gram}$$

Example: A HS bridge spanning 16" weighs 22.5 grams and holds 62 lbs. will perform at 2.75 lbs./gram. A second HS bridge spanning 16" weighs 19.75 grams and holds 58 lbs. will perform at 2.936 lbs./gram. The bridge supporting 58 lbs. will be the winner as a more efficient design.

Design Requirements:

1. Dimension Requirements
 - a. Overall Width must be between 3" minimum - 5" maximum.
 - b. Overall Height must be between 2" min. - 6" maximum.
 - c. Overall Length must be between 16" - 20".
 - overall bridge length must be greater than span to support the bridge on the testing blocks.
2. The bridge must allow a 1-1/2" wide by 2" loading block to descend to the deck surface (roadway) for testing. Loading is applied from below at the center of the spans (see photo page 2).
3. Bridge must have a 1/2" diameter hole at the center of the deck to allow for testing device
4. The bridge shall be constructed of entirely 1/8" x 1/8" balsa or basswood members and glue.
 - Students may laminate members to create stronger elements.
 - Top chord may have up to 2 laminations.
 - Bottom chord may have up to 3 laminations.
 - All interconnecting elements must be single pieces – no laminations allowed
5. The bridge does not need to have a solid "deck" or "roadway" surface, but merely "deck level bracing" for the loading block to bear on.

6. Wood joints may be notched if desired.
7. Any adhesive/glue may be used at the joints of the members.
8. Cantilever supports are allowed to descend up to 1 inch below the surface of either the 16" span.
9. Any combination of balsa or basswood species may be used in construction of the bridge. (*Note to Educators: Field's Hobby in Amherst has low prices on bulk supplies of balsa and basswood stock. Pitsco also has bulk rates at www.pitsco.com)*
10. There is no limitation on the mass of the bridge: however, the most efficient bridges are typically less than 30 grams.
11. Weight of bridge, in grams, must be done prior to student registration at STEM Wars on May 23rd. Weight must be written legibly on bridge. There will be balances/scales present for judges confirmation, but weighing at registration will slow down the testing process.

Awards: Middle and High Schools: First, Second and Third place rated for **Efficiency**.
Individual Awards for **Highest Weight Held**.
Judges Awards for **Excellence in Craftsmanship**

**Please contact Jamie Francisco at jfrancisco@silvercreekschools.org if you have any questions or concerns.

